use of contransmitter Procession Pr	Fee X
SANTA FE Image:	Fee X
FILE U.S. 0.5. LAND OFFICE DPERATOR DPERATOR Stote OIL 6 Gos Longe 1 SUDDRY NOTICES AND REPORTS ON WELLS Stote OIL 6 Gos Longe 1 Use not use this permit concentrated transfer of permitted of an addition of the other other of the other othe other other other othe other other other oth	Fee X
USNOS: State OFFICE OPERATOR S. State OIL & Gras Leave 1 SUNDRY NOTICES AND REPORTS ON WELLS. S. State OIL & Gras Leave 1 Iteo nor ust transformer of transformer of transformer detection d	Fee X
LAND OFFICE DREMATOR Data Street of the street of street of the str	
SUNDRY NOTICES AND REPORTS ON WELLS	No.
1. OTHER. 7. Unit Agreement Nome 2. Name of Operator 8. Form or Lease Name 3. Address of Operator 9. Well No. 7.26 Vaughn Bldg., 'lidland, Texas 1 4. Location of Well 0 UNIT LETTER 0 1980 FEET FROM THE E Line AND 660 10. Field and Pool, or Wilk UNIT LETTER 0 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON PLUG AND ABANDON OTHER CHANGE PLANS	
1. OTHER- 7. Unit Agreement Nome 2. Name of Operator 8. Farm or Lease Name 3. Address of Operator 9. Well No. 7.26 Vaughn Bldg., 21dland, Texas 1 4. Location of Well 9. Well No. with Letter 0 1980 rec 5. Line, section 7. Township 15. Elevation (Show whether DF, RT, GR, etc.) 12. County 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Notice OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. OTHER CHANGE PLANS CAMERE PLANS OTHER CHANGE PLANS CHANGE PLANS OTHER CHANGE PLANS CHANGE PLANS OTHER CHANGE PLANS CHANGE ALTER CASING THE ALL WORK CASING TEST AND CEMENT JOB X PLUG AND ABANDON CHANGE PLANS OTHER CHANGE PLANS CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER CHANGE PLANS CASING TEST AND CEMENT JOB X PLUG AND ABANDO OTHER CHANGE PLANS CASING TEST AND CEMENT JOB X CASING TEST AND CEMENT JOB X <	
Will X All Contrant 2. Name of Operation 6. Form or Lease Name J. C. Williamson Anderson 7 3. Address of Operation 9. Well No. 726 Vaughn Bldg., 'lidland, Texas 1 4. Location of Well 1 untr Letter	
J. C. Williamson Anderson 7 J. Address of Operator 726 Vaughn Bldg., 'lidland, Texas 1 4. Location of Well 1980 1 UNIT LETTER 0 1980 THE 0 1980 THE 0 10. Field and Pool, or Will UNIT LETTER 0 10. Field and Pool, or Will UNIT LETTER 0 115. Elevation (Show whether DF, RT, GR, etc.) 12. County 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PEER ORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ASANDON CHARGE PLANS CASING TEST AND CEMENT JAR X ALTERING CASING 0THER Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 1705. PLUG AND ABANDON CHARGE PLANS 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 1705. Well spudded 1 p.m., 10/28/67 Other 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Casing measured 425,67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium chi lunged down	
3. Address of Operator 9. Well No. 726 Vaughn Bldg., :lidland, Texas 1 4. Location of Well 1980 WHIT LETTER 0 1980 FEET FROM THE E Line AND 660 FEET FROM THE 0 10. Field and Pool, or Will WHIT LETTER 0 11. S Address 12. County Lea 13. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK ALTERING CASING TEMPORARILY ABABON PLUG AND ABANDON PULL ON ALTER CASING CHANGE PLANS 0THER CHANGE PLANS 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 103. Well spudded 1 p.m., 10/28/67 Other Other Aute of 12 Other	
726 Vaughn Bldg., :lidland, Texas 1 726 Vaughn Bldg., :lidland, Texas 1 10. Fleid and Pool, or Wild 10. Fleid and Pool, or Wild unit Letter 0 1980 THE 0 1980 THE 0 11 S 11. S 37 E THE 11 S 12. County 12. County 14. Control of Wild 15. Elevation (Show whether DF, RT, GR, etc.) 12. County 12. County Lea 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON REMEDIAL WORK ALTERING CASING OTHER PLUG AND ABANDON CHANGE PLANS 0THER Change Plans Convert and give pertinent dates, including estimated date of starting a work/ SEE NULE 1703. Well spudded 1 p.m., 10/28/67 Starting a starting a work/ SEE NULE 1703. Well spudded 1 p.m., 10/28/67 11. joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Starting a starting a work/ see nule 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch 10. grade dow at 6:50 a.m. 10/29/67. Start at 300#, held okay. Start at 300#,	
4. Location of Well 0 1980 FEET FROM THE E 660 10. Field and Pool, or Will THE S LINE, SECTION 7 TOWNSHIP 11 S RAMEE 37 E NMPM. 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data 12. County Lea 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PULL OR ALTER CASING PLUG AND ABANDON REMEDIAL WORK ALTERING CASING 0THER CHANGE PLANS CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 1703. Well Spudded 1 p.m., 10/28/67 OTHER Well Spudded 1 p.m., 10/28/67 Starting a work) SE at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch'lugged down at 6:50 a.m. 10/29/67. Torculated 40 sacks cement. aited 24 hours, tested at 500#, held okay.	
UNIT LETTER 0 1980 FEET FROM THE E 660 FEET FROM S 11 S 37 E 11 S 37 E NMPM. 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data 12. County Lea NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON ALTERING CASIM PULL OR ALTER CASING PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON 17. Describe Proposed or Completed Operations (Clearly state all periment details, and give pertiment dates, including estimated date of starting a work) SEE RULE 1703. Well spudded 1 p.m., 10/28/67 OTHER 11. joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Casing the Shoe. Casing the Shoe. Casing the Shoe. an 11 joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. 10/29/67. Casing the Shoe. 10/29/67. Change down at 6:50 a.m. 10/29/67. Ster at 418' with 425 sacks Class C cement, 4% gel, 2% calcium chilling days. 1	dcat
S 11 S 37 E THE Section 7 TOWNBHIP 15 15. Elevation (Show whether DF, RT, GR, etc.) 12. County Lea 4001' DF 12. County Lea 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON PULL OR ALTER CASING CHANGE PLANS OTHER CHANGE PLANS 17. Describe Proposed or Completed Operations (Clearly state all periment details, and give pertiment dates, including estimated date of starting a work) SEE RULE 1703. Well Spudded 1 p.m., 10/28/67 Other casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium chilling down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. inted 24 hours, tested at 500#, held okay.	
15. Elevation (Show whether DF, RT, GR, etc.) 12. County 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK CHANGE PLANS OTHER COMMENCE DRILLING OPNS. OTHER COMMENCE DRILLING OPNS. OTHER CHANGE PLANS OTHER OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 1103. Well spudded 1 p.m., 10/28/67 Other 420' Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium chilling down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Taited 24 hours, tested at 500#, held okay.	IIIII
15. Elevation (Show whether DF, RT, GR, etc.) 12. County 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK PLUG AND ABANDON PULL OR ALTER CASING CHANGE PLANS OTHER CHANGE PLANS 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 1103. Surface casing: Well spudded 1 p.m., 10/28/67 Other 420' Well spudded 1 p.m., 10/28/67 Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium chilling down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Atted 24 hours, tested at 500#, held okay.	
16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASIM TEMPORARILY ABANDON PLUG AND ABANDON REMEDIAL WORK ALTERING CASIM TEMPORARILY ABANDON PLUG AND ABANDON REMEDIAL WORK ALTERING CASIM TEMPORARILY ABANDON PLUG AND ABANDON REMEDIAL WORK ALTERING CASIM TOTHER CHANGE PLANS CHANGE PLANS COMMENCE DRILLING OPNS. TOTHER CHANGE PLANS OTHER PLUG AND ABANDON TOTHER Well spudded 1 p.m., 10/28/67 OTHER OTHER Surface casing: Well spudded 1 p.m., 10/28/67 Surface Casing with Texas Pattern Guide Shoe. Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium childing down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Tirculated 40 sacks cement. Tirculated 24 hours, tested at 500#, held okay.	ΤΠΠ
16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON PLUG AND ABANDON PULL OR ALVER CASING CHANCE PLANS OTHER CHANCE PLANS 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 1703. Surface casing: Well spudded 1 p.m., 10/28/67 Other 420' Start at 418' with 425 sacks Class C cement, 4% gel, 2% calcium chilling down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Intent of the completed at 500#, held okay.	illilli.
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASINI TEMPORARILY ABANDON PULG AND ABANDON REMEDIAL WORK ALTERING CASINI PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB PLUG AND ABANDON 0THER OTHER OTHER OTHER OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 1103. Well spudded l p.m., 10/28/67 Ourface casing: Other 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Starting a casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium childing estimated 40 sacks cement. Casing measured 40 sacks cement. Intervelop/67. Intervelop/67. Calited 24 hours, tested at 500#, held okay. Intervelop/67.	71111
PERFORM REMEDIAL WORK ALTERING CASIN TEMPORARILY ABANDON PULL OR ALTER CASING COmpleted Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 1703. Surface casing: Other Used to find the start of th	
TEMPORARILY ABANDON PLUG AND ABAND PULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. OTHER CHANGE PLANS CASING TEST AND CEMENT JQB OTHER OTHER OTHER I7. Describe Proposed or Completed Operations (Clearly state all perinent details, and give pertinent dates, including estimated date of starting a work) see RULE 1103. Well spudded 1 p.m., 10/28/67 Surface casing: Other Starting a state all perinent details, and give pertinent dates, including estimated date of starting a work) see RULE 1103. Well spudded 1 p.m., 10/28/67 Surface casing: Other Starting a state all perinent details, and give pertinent dates, including estimated date of starting a work) see RULE 1103. Well spudded 1 p.m., 10/28/67 Surface casing: Other Starting a state all perinent details, and give pertinent dates, including estimated date of starting a starting a start depth 420' Well spudded 1 p.m., 10/28/67 Can 11 joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Start 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch' Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch' Start 418 start 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch' Clugged down at 6:50 a.m. 10/29/67. Start 418 start 418 start 418 start 418' with 425 sacks class C cement, 4% gel, 2% calcium ch'	
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER OTHER OTHER OTHER TR. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) see RULE 1103. Surface casing: Otal depth 420' Ran 11 joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch Plug and ABAND OTHER Different dates, including estimated date of starting a Well spudded 1 p.m., 10/28/67 Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch Plug and ABAND OTHER Different dates, including estimated date of starting a Well spudded 1 p.m., 10/28/67 Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch Plug ad down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Vaited 24 hours, tested at 500#, held okay.	r
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JQB OTHER	
OTHER	ONMENT
The proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) see Rule 1103. Well spudded 1 p.m., 10/28/67 Surface casing: Otal depth 420' Can 11 joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch Plugged down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Naited 24 hours, tested at 500#, held okay.	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting a work) SEE RULE 1103. Surface casing: Otal depth 420' Can 11 joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch Plugged down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Naited 24 hours, tested at 500#, held okay.	<u></u>
Well spudded 1 p.m., 10/28/67 Surface casing: Otal depth 420' Can 11 joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch Plugged down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Naited 24 hours, tested at 500#, held okay.	
Well spudded 1 p.m., 10/28/67 otal depth 420 Can 11 joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch Plugged down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Naited 24 hours, tested at 500#, held okay.	ny proposed
Ran 11 joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch Plugged down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Naited 24 hours, tested at 500#, held okay.	
Ran 11 joints of 12 3/4" 34# ST&C casing with Texas Pattern Guide Shoe. Casing measured 425.67', set at 418' with 425 sacks Class C cement, 4% gel, 2% calcium ch Plugged down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Naited 24 hours, tested at 500#, held okay.	
Casing measured 425.67', set at 418' with 425 sacks class c cement, 4% ger, 2% carcium ch Plugged down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Naited 24 hours, tested at 500#, held okay.	
Plugged down at 6:50 a.m. 10/29/67. Circulated 40 sacks cement. Naited 24 hours, tested at 500#, held okay.	loride.
laited 24 hours, tested at 500#, held okay.	
laited 24 hours, tested at 500#, held okay. Now drilling at 4802' in lime.	
low drilling at 4802' in lime.	
WW diffing de tote in finer	
·	
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	

5 IGNED	fullinam	TITLE	Operator	11/6/67
APPROVED BY		TITLE	. <u></u>	DATE

CONDITIONS OF APPROVAL, IF ANYI