NO. OF COPIES RECEIVED		Form C-103
DISTRIBUTION	4	Supersedes Old C+102 and C+103
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE		
U.S.G.S.		5a. Indicate Type of Lease
LAND OFFICE		State X Fee
OPERATOR		5. State Oil & Gas Lease No.  K-2466 & K-1111
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT -" (FORM C-1011 FOR SUCH PROPOSALS.)		
I. OIL X GAS WELL X	OTHER-	7. Unit Agreement Name
2. Name of Operator  The Superior Oil Company		8. Form or Lease Name State "G" Com
P. O. Box 1900, Micland, Texas 79701		9. Well No. <b>1</b>
4. Location of Well		10. Field and Pool, or Wildcat
	1980 FEET FROM THE South LINE AND 660 FEET FRO	Inhe-Permo Penn
UNIT LETTER,,	FEET FROM THE LINE AND FEET FRO	
THE West LINE, SEC	TION 13 TOWNSHIP 10-S HANGE 33-E NMPN	
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
ÄIIIIIIIIIII	RKB: 4,217'	Lea
Check	k Appropriate Box To Indicate Nature of Notice, Report or O	ther Data
		T REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	
	OT+ER	
OTHER		
17. Describe Proposed or Completed work) SEE RULE 1903.	Operations (Clearly state all pertinent details, and give pertinent dates, including	g estimated date of starting any proposed
	above Bough "C" perfs (9714'-9723') at 9630' & Ca	apped w/a 35 sack cement
	Top of cement at 9100'.	7 / 7 /011
2. Shot 4-1/2" casir shot point.	ng at 6314' on 11-22-74. Pulled and recovered al	1 4-1/2" casing above
3. Spotted a 50 sack	c cement plug from 5603' to 5500' in open hole or	11-25-74.
	ll at 5603', could not get tail of tbg any lower.	
4. Spotted a 50 sack	c cement plug from 5497' to 5427' in open hole or	11-25-74.
5. Spotted a 50 sack at 4000' on 11-25	c cement plug from 4013' to 3865' in and out of 85-74.	3-5/8" casing shoe
6. Shot 8-5/8" casir shot point.	ng at 902' on 11-27-74. Pulled and recovered all	8-5/8" casing above
	c cement plug from 902' to 802' at 8-5/8" casing	stub on 11-28-74
8. Spotted a 60 sack	c cement plug from 408' to 300' on 11-28-74. 11-	3/4" casing shoe at 400!
9. Cut off 11-3/4" of	casing head 4 feet below ground level. Placed a asing and installed a dry hole marker in accordan	10 sack cement plug in
11-29-74.	zorno and inscarred a dry note marker in accordan	ice with MMOCO rules on
	n cleaned and leveled and is ready for inspection	l.
	TOT 110 0 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
	PLUGGED AND ABANDONED 11-29-74	

APPROVED BY Attack (Coff TITLE Petroleum Engineer DATE 12-31-74