

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-90
7. Unit Agreement Name
8. Farm or Lease Name State "A"
9. Well No. 2
10. Field and Pool, or Wildcat North Bagley-Lower Penr
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Charles C. Gillespie, Jr.
3. Address of Operator P. O. Box 1179, Midland, Texas 79701
4. Location of Well UNIT LETTER M, 520 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 3 TOWNSHIP 11-S RANGE 33-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4254 G. R.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOBS ☒  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

March 13, 1968  
Spudded Well at 3:00 P. M.

March 14, 1968  
Drilled 15" hole to 360 ft. and ran and cemented 7 jts. of 12 3/4", 38#, new casing to 360 ft. and cemented with 375 sacks Incor Neat w/2% Calcium Chloride. Cement circulated. W.O.C. 18 hrs. Installed B.O.P. Tested casing to 800 psi for 30 min. Held O. K.

March 19, 1968  
Drilled 11" hole to 3785 ft. Ran & Cemented 92 jts. of 8 5/8", 24# & 28#, ST&C new FWP&S casing to 3781.67 ft. and cemented with 350 sacks Incor 6% gel followed by 100 sacks Incor Neat. Plug down @ 11:00 P. M. W.O.C. 18 hrs. Nipped up and installed B.O.P. Pressure tested casing and BOP with 800 psi for 30 min. - Held O. K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Neal Albritton TITLE Agent DATE 4-5-68  
APPROVED BY Joe J. Stoney TITLE Agent DATE APR 8 1968  
CONDITIONS OF APPROVAL, IF ANY: