State of New Mexico Energy, ... inerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT P.O. Box 1980, Hobbs, NM 88240 **OIL CONSERVATION DIVISION** 310 Old Santa Fe Trail, Room 206

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A

DISTRICT P.O. Drawer DD, Artesia, NM \$8210 Santa Fe, New Mexico 87503

VELL API NO.	
30-025-22406	
f. Indiana Toma of Large	

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

STATE XX FEE _ State Oil & Gas Lease No N/A Lease Name or Unit Agreement Name **GRAHAM B STATE**

DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: CAS XX WELL. WELL OTHER Name of Operator 8. Well No. **ENDEAVOR ENERGY RESOURCES, LP** Address of Operator 9. Pool name or Wildcat 110 N. MARIENFELD, SUITE 110, MIDLAND, TEXAS 79705 W. BAGLEY Well Location 660 **EAST** NORTH 660 Unit Letter Feet From The _ Line and Feet From The Line LEA, NEW MEXICO **NMPM** County Section Township 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4313 G.L. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF

PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PLUG AND ABANDONMENT **TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: OTHER ..

- 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

 1. 01/03/2003 NOTIFY OCD SYLVIA O

 Lightiffy stiriday hand to Liability under bond is retained until
- 2. 01/08/2003 SET CIBP AT 8500'.
- 3. CIRCULATED HOLE WITH 10# MLF.
- 4. 25 SACKS OF CEMENT 8500 8122.
- surface restoration is completed. 5. PRESSURED UP ON PERFORATIONS AT 7100 TO 1000 PSI; SPOTTED 25 SACKS OF CEMENT 7150 - 6774.
- 6. PRESSURED UP ON PERFORATIONS AT 5140 TO 1000 PSI; SPOTTED 25 SACKS OF CEMENT 5190 4812.
- 7. 01/110/03 SQUEEZED 55 SACKS OF CEMENT UNDER PACKER AT 3667 THROUGH PERFORATIONS AT 3967 AT 2 BBLS/MIN AT 1200 PSI.
- 8. SPOTTED 40 SACKS OF CEMENT AT 2322 2137; NO NEED TO TAG AS PER OCD BILLY P.
- 9. SPOTTED 40 SACKS OF CEMENT AT 1600 1453; NO TAG AS PER SAME.
- 10. PERFORATED AT 470; SQUEEZED 110 SACKS OF CEMENT UNDER PACKER AT 150 THROUGH PERFORATIONS 257-470 WITH COMMUNICATIONS UP 8 5/8 X 11 3/4 DISPLACED TOC TO 350'; WOC; TAGGED TOC AT 336.
- 11. CUT WELLHEAD
- 12. 10 SACK SURFACE PLUG.
- 13. INSTALLED DRY HOLE MARKER.
- 14. CUT DEAD MAN AND BACKFILLED PITS AND CELLAR.

Approved as to plugging of the Well Bore. Liability under bond is retained until surface restoration is completed.

I hereby cartify that the information above as true and complete to the best of my knowledge and I	cusent	DATE 1-21-05
TYPE OR PRINT NAME HBOST 19ht		TELEPHONE NO 915 - 570 5382

(Thus source for State Use

COMMITTIONS OF APPROVAL, IF ANY

ORIGINAL SIGNED BY GARY W. WINK

OC FIELD REPRESENTATIVE II/STAFF MANAGER

FEB 0 1 2003