

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-7324
7. Unit Agreement Name
8. Farm or Lease Name State
9. Well No. 6
10. Field and Pool, or Wildcat Inbe Perno Penn
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Clar-Don Products Company
3. Address of Operator c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs, N. M. 88240
4. Location of Well UNIT LETTER B , 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 24 TOWNSHIP 10 S RANGE 33 E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4180 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set Cast Iron Bridge Plug @ 9808 w/35' cement on top
Shot 5 1/2" casing @ 6079' and pulled
Spot 100' cement plug across 5 1/2" stub @ 6079 (40 sks - 5979-6079)
Spot 100' cement plug across Glorieta @ 5373 (40 sks - 5323-5423)
Spot 100' cement plug across shoe @ 5/8 @ 4005' (40 sks - 3955-4055)
Cut @ 5/8" casing @ 1590 and 1411 and pulled
Spot 100' cement plug across @ 5/8" stub @ 1411 (60 sks - 1361-1461)
Spot 100' cement plug across 13 3/8 shoe @ 398' (348-448)
10 sks @ surface and installed dry hole marker.
Mud between all plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Herndon* TITLE Agent DATE 1/31/74
APPROVED BY *John W. Runyan* TITLE Geologist DATE FEB 11 1974
CONDITIONS OF APPROVAL, IF ANY: