

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
<b>K-5351</b>	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
<b>Southland Royalty Company</b>		<b>Vada-State</b>
3. Address of Operator		9. Well No.
<b>1405 Wilco Bldg., Midland, TX 79701</b>		<b>1</b>
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <b>D</b> , <b>660</b> FEET FROM THE <b>north</b> LINE AND <b>660</b> FEET FROM		<b>Vada (Penn.)</b>
THE <b>west</b> LINE, SECTION <b>32</b> TOWNSHIP <b>9-S</b> RANGE <b>34-E</b> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
<b>4277.7' GR</b>		<b>Lea</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The following work was done by Permian Basin Casing Pullers, Inc.:

- 3-13-76 Installed "Bomb" in Baker Model "D" packer @ 9795' to convert packer to BP. Spotted 15 sx cement in 5 1/2" casing 9695-9795'.
- 3-16-76 Shot and recovered 4604' of 5 1/2" casing. Spotted 35 sx cement 4498-4650'.
- 3-18-76 Shot and recovered 986' of 8 5/8" casing. Spotted 50 sx cement 922-1036'. Spotted 65 sx cement 325-440'. Spotted 10 sx cement 0-20'.

All plugs placed w/9.5# mud-laden fluid between plugs.  
Installed dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C.H. Can TITLE District Engineer DATE 4-9-76

APPROVED BY [Signature] TITLE OIL FIELD INSPECTOR DATE [Signature]

CONDITIONS OF APPROVAL, IF ANY: