

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
K-5351

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Southland Royalty Company	8. Farm or Lease Name Vada-State
3. Address of Operator 1405 Wilco Bldg., Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER D , 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 9-S RANGE 34-E NMPM.	10. Field and Pool, or Wildcat Undesig. (Vada-Penn. Ext.)
15. Elevation (Show whether DF, RT, GR, etc.) 4277.7	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 7 7/8" hole to T.D. of 9890'. Ran logs. Ran 275 jts 5 1/2" 17# & 20# J-55 & N-80 (used) casing set @ 9890'. Cement w/450 sx Incor 12% gel cement w/8# salt/sx plus 75 sx Incor 2% gel cement w/8# salt/sx. Plug down @ 2 p.m., 4-2-68. T/cement behind 5 1/2" @ 7290' by temperature survey. WOC 24 hrs. Test casing @ 2000 psi for 30 min. - hold O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

BY *C. H. Can* TITLE District Engineer DATE 4-5-68
BY *Joe L. Hines* TITLE SUPV. DATE 4-8-68
INS OF APPROVAL, IF ANY: