

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

HUBBS OFFICE D. C. C.
JUN 3 8 29 AM '68

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS</p> <p align="center">(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/></p> <p>5. State Oil & Gas Lease No. K 3513</p>
<p>1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- DRY HOLE</p>		<p>7. Unit Agreement Name</p>
<p>2. Name of Operator SOUTHWEST PRODUCTION CORPORATION</p>		<p>8. Farm or Lease Name State</p>
<p>3. Address of Operator P. O. Box 936, Roswell, New Mexico 88201</p>		<p>9. Well No. 1</p>
<p>4. Location of Well UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 11S RANGE 35E N.M.P.M.</p>		<p>10. Field and Pool, or Wildcat Wildcat</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) 4174 KB</p>		<p>12. County Lea</p>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-7-68:

Drilled to 10,444 Ft. Ran DST and Logs. Laid down DC, ran DP open ended, set plugs as follows (Approval granted by Mr. Clements by telephone) (Dowell Cementers):
150 sx Class H cement, 10,000' - TD; 25 sx Class H Cement 8,100' - 8,200';
75 sx Class H Cement 4,100' - 4,300' (8-5/8" casing set at 4225'); Laid down DP, moved rig. Drilling mud (9.6#) set between cement plugs.

5-8-68:

Cut 8-5/8" casing and recovered 1097', set 25 sx Class A Cement plug at 1097', set 25 sx Class A Cement Plug at 343' (13-3/8" surface casing set at 343'), cut off casing head, set 10 sx Class A Cement plug at surface w/D H Marker (Knox Services). The pits have been filled, and location levelled and cleared.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. B. Appleton

TITLE Production Manager

DATE May 29, 1968

APPROVED BY John W. Runyan

TITLE Geologist

DATE

MAY 25 1970

CONDITIONS OF APPROVAL, IF ANY: