

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. OG-259

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Shenandoah Oil Corporation	8. Farm or Lease Name Humble State
3. Address of Operator 1018 Commerce Bldg 3rd floor, Tex 76102 2101 W. Wall, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER M, 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 9 TOWNSHIP 11-S RANGE 33E NMPM.	10. Field and Pool, or Wildcat Bagley Pen North
15. Elevation (Show whether DF, RT, GR, etc.) Unknown	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1st plug: Set CI Bridge Plug on wire line 3,880. Put 3 sks cement on top.
2nd plug: Shot 5 1/2 O.D. csg. off 3,785. Spot 40 sks plug from 3,835 to 3,735.
3rd plug: Half in and half out 8 5/8 csg. 40 sks plug from 3,850 to 3,750.
4th plug: 40 sks plug opposite top of salt from 1,854 to 1,754.
5th plug: Shot 8 5/8 csg. off 3,772. 40 sks plug from 728 to 828.
6th plug: 10 sks in top of surface csg.

Welded marker on top of surface csg.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>BN Cray</u>	TITLE <u>District Production Superintendent</u> DATE <u>8/18/76</u>
APPROVED BY <u>W. Patterson</u>	TITLE <u>Oil & Gas Supervisor</u> DATE <u>8/18/76</u>
CONDITIONS OF APPROVAL, IF ANY:	

RECEIVED

APR 13 1976

OIL CONSERVATION COMM.
HOBBS, N. M.