

HOBBS OFFICE O.C.C.

JUN 10 8 21 AM '68

OPERATOR: Paul DeClove

LEASE & WELL NO.: HUMBLE STATE 1

LOCATION: 'W' Sec 9, 11S, 33E

DETAIL OF CASING STRINGS

Surface Casing

370' - 12 3/4" 37# Casing cemented with 275 sacks regular cement
w/ 2% Calcium Chloride. Cement circulated.

Intermediate Casing

0 - 2220' 24# J-55 8 5/8" casing
2220 - 3722' 32# J-55 8 5/8" casing

Cemented with 150 sacks Incor Pozmix w/2% Gel
and 2% Calcium Chloride and 150 sacks neat cement.

Production Casing

0	-	1921.50	23#	N-80	5 1/2"	Youngstown Speedtite Casing
1921.50	-	1964.38	20#	N-80	5 1/2"	LT&C Casing
1964.38	-	8043.28	17#	N-80	5 1/2"	LT&C Casing
8043.28	-	10353.39	20#	N-80	5 1/2"	LT&C Casing

Casing was sand coated and equipped with scratchers
through the pay section.

Cemented with 500 sacks Incor Pozmix w/2% gel and
8% salt per sack with 3/4 of 1% CFR-2 in first
250 sacks.

HOBBS OFFICE O.C.C.

PM 10 8 51 AM '68

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE

RECEIVED TELETYPE