

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 06-259

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Paul DeCleva	8. Farm or Lease Name Humble State
3. Address of Operator 102 Oil Center, Wichita Falls, Texas 76302	9. Well No. 1
4. Location of Well UNIT LETTER M, 660 FEET FROM THE South LINE AND 660 FEET FROM west LINE, SECTION 9 TOWNSHIP 11-S RANGE 33-E NMPM.	10. Field and Pool, or Wildcat No. Bagley (Lower Penn)
15. Elevation (Show whether DF, RT, GR, etc.) 4290 Ground	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Surface Casing: Set and cemented as follows on March 20, 1968:

Hole Size: 17-1/2"

Casing: 370' of 12-3/4", 37# (Grade X-42 with maximum WP of 1330#)

Cement: 275 sacks of regular cement with 2% CaCl. Cement Circulated. WOC 18 hours. Tested at 600 psi for 30 minutes, no pressure drop.

Intermediate Casing: Set and cemented as follows on March 24, 1968:

Hole Size: 11"

Casing: 3722' of 8-5/8" as follows: 0' to 12' DF correction, 12' to 2220' - 24#, 2220' To 3722' - 32# (both the 24# and 32# are Grade J-55)

Cement: 150 sacks Incor Posmix with 2% gel and 2% CaCl and tailed-in with 150 sacks Neat with 2% CaCl. WOC 24 hours. Tested at 1500 psi for thirty minutes, no pressure drop.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H.L. McCracken TITLE H.L. McCracken, Engineer DATE 3-27-68
APPROVED BY Joe J. Hines TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: