

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| |
|--|
| 5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/> |
| 5. State Oil & Gas Lease No. E-7324 |
| 7. Unit Agreement Name |
| 8. Farm or Lease Name State |
| 9. Well No. 7 |
| 10. Field and Pool, or Wildcat Undesignated |
| 12. County Lea |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
The Louisiana Land and Exploration Company

3. Address of Operator
1605 Wilco Building, Midlnd, Texas 79701

4. Location of Well
UNIT LETTER **A**, **660** FEET FROM THE **north** LINE AND **660** FEET FROM
THE **east** LINE, SECTION **24** TOWNSHIP **10-S** RANGE **33-E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
4185' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

| NOTICE OF INTENTION TO: | | SUBSEQUENT REPORT OF: | |
|--|---|--|---|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | OTHER <input type="checkbox"/> | CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> | OTHER <input type="checkbox"/> |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 295 jts (9911') 5 1/2" 17# J-55 and N-80 casing. Set @ 9925' with 150 sx 6% gel, 15# salt/sk, 3/4% CFR-2 and 125 sx Incor 11# salt/sk, 3/4% CFR-2.

Plug down @ 10:25 PM 4-16-68. Bumped plug with 2000#, released pressure, float held OK. WOC 48 hours.

Ran temperature survey - top of cement @ 8540. Maximum instrument depth 9900'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *F. H. Reiter* TITLE Geologist DATE April 18, 1968
F. H. Reiter

APPROVED BY *[Signature]* TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: