	1		
NO. OF COPIES RECEIVED		Form C-103 Supersedes Old	
DISTRIBUTION		C-102 and C-103	
SANTA FE	NEW MEXICO OIL CONS	Effective 1-1-65	
FILE			
U.S.G.S.			State X Fee
LAND OFFICE			
OPERATOR			5. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIN. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)			
1. OIL X GAS WELL X	OTHER-		7. Unit Agreement Name
2. Name of Operator			8. Farm or Lease Name
The Louisiana Land and Exploration Company			State
3. Address of Operator			9. Well No.
1605 Wilco Building, Midland, Texas 79701			7
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTERA	660 FEET FROM THE north	LINE AND 660 FEET	Undesignated Undesignated
THE <u>east</u> LINE, SECTI	on <u>24</u> township <u>10S</u>	RANGE 33E	имрм. () () () () () () () () () () () () ()
		DE PT CP	10 Country
	15. Elevation (Show whether		12. County
ČIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	4185'		l lea (\\\\\\\\
	Appropriate Box To Indicate Notention To:	_	JENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB]
		OTHER	
OTHER			
17. Describe Proposed or Completed Owork) SEE RULE 1705.	perations (Clearly state all pertinent det	ails, and give pertinent dates, inc	luding estimated date of starting any proposed
Spudded 12:15	AM CST 3-17-68.		
Ran 14 its. ne	w 13 3/8" 48# H -4 0 casin	g. Set @ 430' with :	350 sx Incor with 2%
CaCl. Cirmla	ted to surface. Approxim	mate temperature of o	ement slurry when mixed
60° F. Estima	ted minimum formation te	mperature 70° F. Est	timate of cement strength
after 12 hours 800 . WOC 12 hours before test. Tested casing with 800 for 30			
min. Test OK.			
Ran 128 jts. (4016.91') new 8 5/8" cas	ing. (Approximately	2450' 24# J-55, 200' 32#
$J_{-}55$, 575' 32 $\#$ H-40, 775' 32 $\#$ J-55.) Set @ 4027' and cemented with 200 sx Incor			
50-50 Poz with	4# salt/sack and 100 sx	Incor with 2% CaCl	& 4# salt/sack. Plug down
at 4:50 AM CST	3-22-68. Bumped plug w	ith 1150#. Released	pressure. Float held
OK. After 8 hours ran temperature survey. Top of cement @ 3350'. WOC 24 hours.			
Tested casing to 1000#. OK.			
	1		
	/		
18. I hereby certary that the information	shove is true and complete to the best	of my knowledge and belief.	
1 / Lt			
8 1d. Red	J. Daitan	Coologist	368

CONDITIONS OF APPROVAL, IF ANY: