

NO OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

HOBBS OFFICE O. C. C.  
NEW MEXICO OIL CONSERVATION COMMISSION

May 14 11 30 AM '68

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>K-1033</b>
7. Unit Agreement Name
8. Farm or Lease Name <b>O'Neill State</b>
9. Well No. <b>1</b>
10. Field and Pool, or Wildcat <b>Undesignated</b>
12. County <b>Lea</b>

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-
2. Name of Operator <b>H. C. HOOD</b>
3. Address of Operator <b>522 Bank of the Southwest, Midland, Texas 79701</b>
4. Location of Well UNIT LETTER <b>0</b> <b>660</b> FEET FROM THE <b>South</b> LINE AND <b>1980</b> FEET FROM <b>East</b> LINE, SECTION <b>24</b> TOWNSHIP <b>10-S</b> RANGE <b>33-E</b> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) <b>4205' Gr</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth 9940'.  
Ran 306 jnts. of 11/60# J-55 4 1/2" csg. Set at 9940'. Cemented with 400 sx Incor Pozmix plus 2% gel plus 11# salt per sack. Plug down at 11:15 P.M. 5-5-68. WOC 48 hrs. Tested with 2000# 30 mins. Held okay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John W. Runyan TITLE **Agent** DATE **May 13, 1968**

APPROVED BY John W. Runyan TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: