

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E9669

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator KKA Corporation	8. Farm or Lease Name New Mexico "CC" St.
3. Address of Operator 405 Wall Towers East - Midland, Texas 79701	9. Well No. 3
4. Location of Well UNIT LETTER <u>C</u> <u>2065</u> FEET FROM THE <u>West</u> LINE AND <u>660</u> FEET FROM THE <u>North</u> LINE, SECTION <u>27</u> TOWNSHIP <u>10-S</u> RANGE <u>33-E</u> NMPM.	10. Field and Pool, or Wildcat Inbe Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4214 DF	12. County Lea

### 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

### PLUGGING PROCEDURE:

- 30 sk cement plug @9650' perf. 9709-9721. Fill hole w/9.5 laden fluid. 25 x 6 1/2" / 100 bbl's
- Top of Cement behind 5 1/2" csg. @7800'.
- Pull 5 1/2" csg. form approx. 7700'.
- 20 sk cement plug on top of 5 1/2" stub.
- 20 sk cement plug @5350' - Top of Glorieta.
- 20 sk cement plug @4102' - Bottom of 8-5/8" csg.
- Pull 8-5/8" csg. form approx. 1000' - 20 sk plug @stub.
- 20 sk plug @base of 11-3/4 csg. 373'.
- 10 sk plug top of 11-3/4" csg.; set marker; clean up location.

*All plugs 100' length*  
*24 hr notice prior to setting plugs*

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Marion Godwin TITLE Agent DATE Oct. 17, 1972

APPROVED BY Joe D. Ramey TITLE Dist. I, Supv. DATE OCT 19 1972  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

6 13 1972

OIL CONSERVATION COMM.  
WASHINGTON