

R-3397 NSL No more than 60% yellow.

|                             |  |                  |  |               |  |
|-----------------------------|--|------------------|--|---------------|--|
| COUNTY LEA                  |  | FIELD Flying "M" |  | STATE NM      |  |
| OPR. SOUTHLAND ROYALTY CO.  |  |                  |  | MAP           |  |
| 2 McCoy, O. C.              |  |                  |  |               |  |
| Sec. 28, T-9-S, R-32-E      |  |                  |  | CO-ORD        |  |
| 800' FSL, 2120' FEL of Sec. |  |                  |  | 30-025-22522  |  |
| Spd 4-15-68                 |  | CLASS            |  | EL [REDACTED] |  |
| Cmp 5-12-68                 |  | FORMATION        |  | DATUM         |  |
| CSG & SX - TUBING           |  | FORMATION        |  | DATUM         |  |
| 8 5/8" 361' 200             |  |                  |  |               |  |
| 5 1/2" 4600' 350            |  |                  |  |               |  |
| LOGS EL GR RA IND HC A      |  |                  |  |               |  |
|                             |  | TD 4600'         |  |               |  |

IP SA Perfs 4492-4521' Pmpd 126 BOPD. Pot. Based on 24 hr test, Gravity 17.2, GOR 527.

Distribution limited and publication prohibited by subscribers' agreement.  
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

|       |            |       |      |    |
|-------|------------|-------|------|----|
| CONT. | PROP DEPTH | 4700' | TYPE | RT |
| DATE  |            |       |      |    |

F.R. 4-18-68  
PD 4700' - SA  
4-22-68 Drlg. 4290' lm.  
4-29-68 TD 4600', prep Acid.  
Perf 4492-96', 4507', 4512', 4518', 4521'  
W/2 SPI  
Acid (4492-4521') 1000 gals (MA) (Tubing leaked)  
5-6-68 TD 4600', prep to RU Pump  
Acid (4492-4521') 4000 gals.  
Swbd load + 90% oil in 4½ hrs.  
5-13-68 TD 4600', COMPLETE  
LOG: SA 4329', SA Porosity 4492'