

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

HOBBS OFFICE O. C. C.

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JUL 9 11 36 AM '68

JUL 0

AM '68

Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

OG 4755

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cayman Corporation	8. Farm or Lease Name Murphy - State "A"
3. Address of Operator P.O. Box 2099, Palos Verdes Peninsula, California 90274	9. Well No. 2
4. Location of Well UNIT LETTER I , 1980 FEET FROM THE South LINE AND 510 FEET FROM THE East LINE, SECTION 21 TOWNSHIP 10-S RANGE 33-E NMPM.	10. Field and Pool, or Wildcat UNDESIGNATED
15. Elevation (Show whether DF, RT, GR, etc.) 4197 GR	12. County Lee

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-2-68 TD 9669' Ran 286 joints 5 1/2", 17# casing as follows:

Top 870.82' J-55 Butt.
1522.75' J-55 LT&C
4777.11' J-55 ST&C
2487.42' N-80 LT&C

Cemented with 535 sx Incor-Pox with 2% gel and 3/4# CFR-2/sx and 8# salt/sx. Plug down 8 PM

6-5-68 TD 9669' WOC 64 hrs. Tested casing with 3000# for 30 min. No leaks.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>[Signature]</i>	TITLE <i>Engineer</i>	DATE <i>7-5-68</i>
APPROVED BY <i>[Signature]</i>	TITLE <i>Supervisor</i>	DATE <i>7-5-68</i>
CONDITIONS OF APPROVAL, IF ANY:		