

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/></p>
<p>1. Name of Operator Cayman Corporation</p>		<p>5. State Oil & Gas Lease No. OG-4755</p>
<p>2. Address of Operator 1206 Wilco's Building, Midland, Texas 79701</p>		<p>7. Unit Agreement Name</p>
<p>3. Location of Well UNIT LETTER <u>L</u> <u>1930</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>24</u> TOWNSHIP <u>10-S</u> RANGE <u>33-E</u> N.M.P.M.</p>		<p>8. Farm or Lease Name Murphy "A" State Com</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) 4207 GL</p>		<p>9. Well No. 3</p>
<p>12. County Lea</p>		<p>10. Field and Pool, or Wildcat Inbe Permo Peen</p>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

<p>NOTICE OF INTENTION TO:</p>		<p>SUBSEQUENT REPORT OF:</p>	
<p>PERFORM REMEDIAL WORK <input type="checkbox"/></p>	<p>PLUG AND ABANDON <input type="checkbox"/></p>	<p>REMEDIAL WORK <input type="checkbox"/></p>	<p>ALTERING CASING <input type="checkbox"/></p>
<p>TEMPORARILY ABANDON <input type="checkbox"/></p>	<p>CHANGE PLANS <input type="checkbox"/></p>	<p>COMMENCE DRILLING OPNS. <input type="checkbox"/></p>	<p>PLUG AND ABANDONMENT <input checked="" type="checkbox"/></p>
<p>PULL OR ALTER CASING <input type="checkbox"/></p>	<p>OTHER <input type="checkbox"/></p>	<p>CASING TEST AND CEMENT JOB <input type="checkbox"/></p>	<p>OTHER <input type="checkbox"/></p>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-8-71 Pumped 35 sx cement plug down tubing at 9810'

3-15-71 Shot into and recovered 4841' of 5-1/2"-17# casing. Placed 25 sx cement plugs at 4770' and 4020'

3-17-71 Shot into and recovered 1000' of 8-5/8" 24# casing. Placed 25 sx cement plugs at 1000' and 390' and a 10 sx cement plug at the surface
Installed marker
8.8 lb. per gal mud between plugs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John W. Rungman TITLE Engineer DATE 4-22-71

APPROVED BY John W. Rungman TITLE Engineer DATE 4-22-71

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 23 1971

OIL CONSERVATION COMM.
HOBBS, N. M.