

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.3.S.		
LAND OFFICE		
OPERATOR		

HOBBS OFFICE O. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION
May 21 11 34 AM '68

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. K-5442	
7. Unit Agreement Name	
8. Farm or Lease Name T. P. State	
9. Well No. 1	
10. Field and Pool, or Wildcat Undesignated	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator H. C. HOOD
3. Address of Operator 522 Bank of the Southwest, Midland, Texas 79701
4. Location of Well UNIT LETTER D , 766 FEET FROM THE North LINE AND 766 FEET FROM THE West LINE, SECTION 25 TOWNSHIP 10-S RANGE 33-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4208' Gr (Est.)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 11:30 A.M. 5-13-68.

Ran 8 jnts. 12 3/4", 34#, H-40 csg. Set at 350'. Cemented with 400 sx Incoor, 2% CaCl. Plug down at 11:45 P.M. 5-13-68, WOC 18 hrs. Pressure tested with 800# 30 min. Held okay. *Circulated ???*

Ran 94 jnts. 8 5/8", 24# & 32#, J-55 csg. Set at 3950'. Cemented with 250 sx. reg., 4% gel, plus 100 sx. reg., 2% CaCl. Plug down at 11:15 A.M. 5-18-68. WOC 18 hrs. Pressure tested with 1200# 30 min. Held okay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Lesley M. Fisk* TITLE Agent DATE May 20, 1968

APPROVED BY *John W. Runyan* TITLE Geologist DATE _____
CONDITIONS OF APPROVAL, IF ANY:

3.0.0 11 15 YAM
83' MA 02 11 15 YAM