

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

HOBBS OFFICE O.C.C.
NEW MEXICO OIL CONSERVATION COMMISSION
MAY 31 8 31 AM '68

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. OG2392
7. Unit Agreement Name
8. Farm or Lease Name State 36
9. Well No. 2
10. Field and Pool, or Wildcat Inbe Permo Penn
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator McGrath & Smith, Inc.
3. Address of Operator 310 West Texas Suite 418 Midland, Texas
4. Location of Well UNIT LETTER <u>J</u> <u>2080'</u> FEET FROM THE <u>East</u> LINE AND <u>1980</u> FEET FROM THE <u>South</u> LINE, SECTION <u>36</u> TOWNSHIP <u>10S</u> RANGE <u>33E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) GL 4207 KB 4219

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 6 p.m., 5-16-68
Drilled 17½" hole to 373'
Cmtd. 13-3/8 - 48#-H40-ST&C Casing at 367' with 375 sx. Incor. with 2% Calcim Chloride Cemented circulating. Plug down 7 a.m., 5-17-68. WOC 12 hrs. Tested 13-3/8 to 800 psi-ok
Drilled 11" hole to 4005'
Cemented 8-5/8-24#&32#-J55-ST&C-casing at 4005' with 500 sx. Incor. Plug down 9:36 a.m. 5-23-68. WOC 18 hrs. Tested 8-5/8 csg. with 1500 psi for 30 min. held o.k.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. B. Caylor TITLE Engineer DATE May 28, 1968
APPROVED BY [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____