

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O.C.G.
NEW MEXICO OIL CONSERVATION COMMISSION
JUN 6 11 38 AM '68

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
OG-424-4

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Paul DeCleva	8. Farm or Lease Name Bagley State
3. Address of Operator 102 Oil Center, Wichita Falls, Texas	9. Well No. 1
4. Location of Well UNIT LETTER D , 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 34 TOWNSHIP 11S RANGE 33E NMPM.	10. Field and Pool, or Wildcat Bagley Penn.
15. Elevation (Show whether DF, RT, GR, etc.) 4279 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Intermediate Casing

Drilled 11" hole from surface casing (379') to 3800', ran 3799' of 8-5/8" casing (2236' of 24# J-55 and 1563' of 32#, J-55) and cemented with 150 sacks posmix with 2% gel and 2% CaCl plus 200 sacks regular cement with 2% CaCl on 5-22-68. WOC for 16 hours. Test to 1500 psi on 5-23-68. No pressure drop.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. L. McCracken TITLE H. L. McCracken, Engineer DATE June 1, 1968

APPROVED BY [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: