

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.
K-363

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- P & A	7. Unit Agreement Name
2. Name of Operator Atlantic Richfield Company	8. Farm or Lease Name Hanagan State
3. Address of Operator P. O. Box 1978, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER E, 1980 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 17 TOWNSHIP 10-S RANGE 34-E NMPM.	10. Field and Pool, or Wildcat Vada-Penn.
15. Elevation (Show whether DF, RT, GR, etc.) 4243' DF	12. County Lea

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

### 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has been plugged and abandoned as follows: Placed DR plug in 415-D packer @ 9887' and spotted 15 sack Class "A" cement plug on top of DR plug (9762-9887'). Shot off 5½" casing @ 7015' WLM and pulled 215 jts 5½" casing. Spotted 60 sack Class "A" cement plug from 5349-5549' and 30 sack Class "A" cement plug 3992-4092'. Shot off 8-5/8" casing @ 1010', pulled 32 jts 8-5/8" 24# casing. Spotted 30 sack Class "A" cement plug from 960-1023' and 30 sack cement plug from 375-425' and 10 sack cement plug from surface to 15'. Erected dry hole marker. 9#/gal salt gel mud was used to spot all plugs. Well P&A 12/4/70.

The above change in plans verbally approved by Mr. Pamey 12/1/70.

Your office will be notified when location is ready for inspection.

### 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.D. Swicker TITLE Dist. Dirg. Supervisor DATE 12/9/70

APPROVED BY John W. Ramsey TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: