

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION, C. O.

JUL 16 12 59 PM '68

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K 4667	
7. Unit Agreement Name	
8. Farm or Lease Name	
Harris State "17"	
9. Well No.	
2	
10. Field and Pool, or Wildcat	
Undesignated	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Pennzoil United, Inc.
3. Address of Operator
P. O. Drawer 1828 - Midland, Texas 79701
4. Location of Well
UNIT LETTER <u>K</u> , <u>2130</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM
THE <u>West</u> LINE, SECTION <u>17</u> TOWNSHIP <u>11-S</u> RANGE <u>34-E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
4188.8 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-23-68 Spudded 17½" hole at 7:00 PM

6-24-68 Drilled to 402' - Ran 12 jts. 13 3/8" OD, 48# casq. - Set @ 392' - cemented w/ 175 sx Class "H" 6% gel plus 150 sx Class "H" 2% HA5. Plug down @ 8:45 AM - Cement circulated OK

6-25-68 After 18 hrs WOC - tested casing w/1,000# for 30 min - OK.

6-29-68 Drilled 11" hole 4250' - Ran 127 jts 8 5/8" OD, 24# & 32# casq. to 4050' - Cemented w/400 sx Class "H" 50/50 posmix w/6% gel & 11# salt per sack plus 150 sx Class "H" w/8# salt per sack. Plug down 6:45 AM 6-29-68

6-30-68 After 28 hours WOC - tested casing w/1500# for 30 min - OK
Top cement by temperature survey 1980'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Drilling Superintendent DATE 7-15-68

APPROVED BY [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: