

NEW MEXICO OIL CONSERVATION COMMISSION

Aug 20 2 40 PM '68

Form C-101
Supersedes Old
C-102 and C-103
Effective 1-1-65

DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.
OG 2392

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. Name of Operator	2. Name of Operator	3. Address of Operator	4. Location of Well	5. Unit Agreement Name	6. Farm or Lease Name	7. Well No.	8. Field and Pool, or Wildcat	9. County
Major, Giebel & Forster	Major, Giebel & Forster	1126 Vaughn Building, Midland, Texas 79701	UNIT LETTER <u>O</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>10-S</u> RANGE <u>33-E</u> NMPM.		T. P. State	1	Undesignated	Lea
15. Elevation (Show whether DF, RT, GR, etc.)								
4215 GR								

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <u>Perforate & acidize</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 7/30/68 Drilled 7 7/8" hole to TD at 9960 feet.
- 7/31/68 Cemented 5 1/2" 17# N-80 & J-55 csg at 9960' with 400 sx cement. Plug down at 5:00 a.m. W.O.C.
- 8/5/68 Tested casing to 2000 #. OK. Spotted 500 gallons 15% DS-30 acid on bottom. Perforated 5 1/2" casing with 2 JSPF from 9931' to 9939'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>William A. Kern</u>	TITLE <u>Engineer</u>	DATE <u>August 19, 1968</u>
APPROVED BY <u>Leslie A. Clements</u>	TITLE <u>Oil & Gas Inspector</u>	DATE <u>10</u>
CONDITIONS OF APPROVAL, IF ANY:		