

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
 JUL 11 11 27 AM '68

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 00 4898
7. Unit Agreement Name
8. Farm or Lease Name Murphy-State
9. Well No. 2
10. Field and Pool, or Wildcat Inbe-Perno Penn
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>
2. Name of Operator Cayman Corporation
3. Address of Operator P.O. Box 2099, Palos Verdes Peninsula, California 90274
4. Location of Well UNIT LETTER J 2002.5 FEET FROM THE East LINE AND 1976.4 FEET FROM THE South LINE, SECTION 13 TOWNSHIP 10-S RANGE 33-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4188.6 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-29-68 Well spudded 5:00 PM

6-30-68 TD 418' Ran 13 joints 13-3/8", 48#, H-40 casing at 418' Cemented with 400 sx Atlas H cement with 2% CaCl. Circulated approximately 40 sx cement. Plug down at 3:30 AM

7-1-68 TD 418' WOC 18 hrs. Tested casing with 800# for 30 min. No leaks.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>W. Goodrich</i>	TITLE <i>Engineer</i>	DATE <i>7-8-68</i>
APPROVED BY <i>John D. Ramey</i>	TITLE <i>Secretary</i>	DATE <i></i>
CONDITIONS OF APPROVAL, IF ANY:		