NO. OF COPIES RECEIVED "CORRECTED REPORT"	Form C-103 Supersedes Old		
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65		
FILE	Ellective 1-1-05		
U.S.G.S. AUG. 7 10 4 AN 368	5a. Indicate Type of Lease		
LAND OFFICE	State Fee		
OPERATOR .	5. State Oil & Gas Lease No.		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)			
I. OIL GAS GAS WELL OTHER-	7. Unit Agreement Name		
2. Name of Operator Coastal States Gas Producing Company	8. Farm or Lease Name Ainsworth "33"		
3. Address of Operator	9. Well No.		
Box 235 Midland, Texas 79701 4. Location of Well	2 10. Field and Pool, or Wildcat		
UNIT LETTER J 2121 FEET FROM THE South LINE AND 1839	Undesignated		
East <u>33</u> Township <u>9S</u> <u>33E</u> NMP			
15. Elevation (Show whether DF, RT, GR, etc.)	12. County		
4290.0 GR	Lea		
TEMPORARILY ABANDON COMMENCE DRILLING OPNS. PULL OR ALTER CASING COMMENCE DRILLING OPNS. OTHER OTHER	PLUG AND ABANDONMENT		
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1103.	ng estimated date of starting any prop		
SPUD DATE: 7/28/68			
7/28/68: Ran 9 joints of 8-5/8" 24#,8R, J-55 ST&C casing set at			
200 sacks of Class "A" 2% CaCl. Cement circulated. Pl casing with 1000#, held ok. WOC 12 hours.	fat fill p.m. lested		
200 sacks of Class "A" 2% CaCl. Cement circulated. PI	at 9.15 p.m. Tested		
 200 sacks of Class "A" 2% CaCl. Cement circulated. PI casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 	at 9.15 p.m. Tested		
 200 sacks of Class "A" 2% CaCl. Cement circulated. PI casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 2. Lone Star Class "A" cement with 2% CaCl. 	at 9.15 p.m. Tested		
 200 sacks of Class "A" 2% CaCl. Cement circulated. PI casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 2. Lone Star Class "A" cement with 2% CaCl. 3. Approximate temperature of slurry - 80°. 	at 9.15 p.m. Tested		
 200 sacks of Class "A" 2% CaCl. Cement circulated. PI casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 2. Lone Star Class "A" cement with 2% CaCl. 3. Approximate temperature of slurry - 80°. 4. Estimated minimum formation temperature - 95°. 			
 200 sacks of Class "A" 2% CaCl. Cement circulated. PI casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 2. Lone Star Class "A" cement with 2% CaCl. 3. Approximate temperature of slurry - 80°. 4. Estimated minimum formation temperature - 95°. 5. Estimate of strength at time of testing - 1020# per square in 	ich.		
 200 sacks of Class "A" 2% CaCl. Cement circulated. PI casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 2. Lone Star Class "A" cement with 2% CaCl. 3. Approximate temperature of slurry - 80°. 4. Estimated minimum formation temperature - 95°. 	ich.		
 200 sacks of Class "A" 2% CaCl. Cement circulated. PI casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 2. Lone Star Class "A" cement with 2% CaCl. 3. Approximate temperature of slurry - 80°. 4. Estimated minimum formation temperature - 95°. 5. Estimate of strength at time of testing - 1020# per square in 6. Actual time in place prior to starting cement test - 12 hours 	ich.		
 200 sacks of Class "A" 2% CaCl. Cement circulated. PI casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 2. Lone Star Class "A" cement with 2% CaCl. 3. Approximate temperature of slurry - 80°. 4. Estimated minimum formation temperature - 95°. 5. Estimate of strength at time of testing - 1020# per square in 	ich.		
 200 sacks of Class "A" 2% CaCl. Cement circulated. Pl casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 2. Lone Star Class "A" cement with 2% CaCl. 3. Approximate temperature of slurry - 80°. 4. Estimated minimum formation temperature - 95°. 5. Estimate of strength at time of testing - 1020# per square in 6. Actual time in place prior to starting cement test - 12 hours To report correct spud and casing setting date. 	ich.		
 200 sacks of Class "A" 2% CaCl. Cement circulated. PI casing with 1000#, held ok. WOC 12 hours. CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS: 1. Volume of cement slurry - 242 cubic feet. 2. Lone Star Class "A" cement with 2% CaCl. 3. Approximate temperature of slurry - 80°. 4. Estimated minimum formation temperature - 95°. 5. Estimate of strength at time of testing - 1020# per square in 6. Actual time in place prior to starting cement test - 12 hours 	August 6. 1968		
 200 sacks of Class "A" 2% CaCl. Cement circulated. Pl casing with 1000#, held ok. WOC 12 hours. <u>CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS</u>: Volume of cement slurry - 242 cubic feet. Lone Star Class "A" cement with 2% CaCl. Approximate temperature of slurry - 80°. Estimated minimum formation temperature - 95°. Estimate of strength at time of testing - 1020# per square ir Actual time in place prior to starting cement test - 12 hours 18. I hereby certify that the information above is true and gomplete to the best of my knowledge and belief. 	ich.		
 200 sacks of Class "A" 2% CaCl. Cement circulated. Pl casing with 1000#, held ok. WOC 12 hours. <u>CASING WAS CEMENTED WITH OPTION NO. 2 AS FOLLOWS</u>: Volume of cement slurry - 242 cubic feet. Lone Star Class "A" cement with 2% CaCl. Approximate temperature of slurry - 80°. Estimated minimum formation temperature - 95°. Estimate of strength at time of testing - 1020# per square ir Actual time in place prior to starting cement test - 12 hours 16. I hereby certify that the information above is true and gomplete to the best of my knowledge and belief. 	August 6. 1968		

	~~	APPROVAL,	1.5	- A & I V
CNDITIONS	~~~	APPROVAL.	1 -	

.