N. M. OIL CONS. COMMISSION P. O. BOX 1080		
Form 9-331 Dec. 1973 HOBBS. NEW MEXICO 88240	Form Approved. Budget Bureau No. 42–R1424	
UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	NM_0269264B & NM 0336039	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas other	Midwest "G" Fed. Oil Com.	
	9. WELL NO.	
2. NAME OF OPERATOR	1	
<u>Amoco Production Company</u>	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Vada Penn	
P. 0. Box 68, Hobbs, NM 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	31-9-34	
AT SURFACE: 1980' FNL X 1980' FWL, Unit K	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL: Sec. 31, T-9-S, R-34-E	Lea NM	
AT TOTAL DEPTH:	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	· · · · · · · · · · · · · · · · · · ·	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
PEOLEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	4291' PBD	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF Image: Constraint of the second seco	DAS CAUSURVEN NY MEXICO	

Propose to acidize to clean out perforations and restore production as follows: Pull rods and pump. Release tubing anchor and tag bottom. Run sand pump and clean to plug back depth of 9806'. Run 2-3/8" tubing and treating packer with 2 joints of tailpipe. Land tailpipe at 9782' and set packer. Acidize with 2000 gal. 15% NEFE HCL mixed with 200 gal. Nalco Visco 1176 at 1-2 BPM. Flush to perfs with 50 bbl formation water. Swab back load. Run tubing, seating nipple, and tubing anchor. Land seating nipple at 9794' with tubing anchor 3 joints above seating nipple. Run rods and pump. Return well to production. (Verbal approval by Armando Lopez on 12-11-81.)

0+4-USGS, R 1-Hou 1-Susp 1-CLF	. And the second	·
Subsurface Safety Valve: Manu. and Type	Set @	Ft.
18. I hereby certify that the foregoing is true and correct SIGNED (attraction to the state of t	12-14-81	
(Drig. Sed.) PETFE W. CHESTER APPROVED BY		
CONDITIONS OF APPROVAL, DEC 1 7 1981 FOR JAMES A. GILLHAM DISTRICT SUPERVISORE Instructions on Reverse Side		
