

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instruction
verse side)

COPY TO O.C.C.
Form Approved
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.
NM 0149818

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

COLL-FEDERAL COM

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

VADA BOUGH C

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

8 9S 35E NMPM

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

TENNECO OIL COMPANY

3. ADDRESS OF OPERATOR

Box 1031 MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' ENL: 1980' FEL SEC 8 T9S R35E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4186 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SPUD 6:30 PM 10-12-68

0-13-68 DRILLED 17 1/2' HOLE TO 350'. RAN 12 JTS 13 3/8 48# H-40 CASING
SET AT 350'. CEMENTED WITH 250SX 50-50 POLMIX CLASS C
INCOR W/2% CaCl₂ AND 1/4#/SX FLOCCE IN FIRST 100SX
AND 100SX CLASS C W/2% CaCl₂. CEMENT CIRCULATED
PLUG DOWN 6:30 AM - WOC 24 HRS - TESTED CASING TO 800#
for 30 MINUTES - HELD O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

Monard K. Karsach

TITLE

Sr. Prod. Clerk

DATE

10-24-68

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

OCT 24 1968

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER