

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <i>Tenneco Oil Company</i>	8. Farm or Lease Name <i>Bonds, et al, F.C.</i>
3. Address of Operator <i>Box 1031 - Midland, Tex. 79701</i>	9. Well No. <i>1</i>
4. Location of Well UNIT LETTER <i>M</i> <i>660</i> FEET FROM THE <i>South</i> LINE AND <i>660</i> FEET FROM THE <i>West</i> LINE, SECTION <i>20</i> TOWNSHIP <i>9</i> RANGE <i>35</i> NMPM.	10. Field and Pool, or Wildcat <i>Wada Penn</i>
15. Elevation (Show whether DF, RT, GR, etc.) <i>4165 GR</i>	12. County <i>Lea</i>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER *Re-enter & complete in San Andres* ☒
(See C-101 dated 2-2-72)

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-4 - 9830' TD - Removed dry hole marker. Drilled out T plug & plug @ 3575'
2-7 - Cleaned out & ran 44 ft of 4 1/2", 11.6#, J-55, casing liner. Cemented w/350#.
Top of liner hanger @ 3739. Pumped plug to 5109'
Mixing temp. 39°, Slurry volume 504 cu. ft. Formation temp 110°. Compression strength 1200 psi. WOC 24 hrs.
2-9 - Cleaned out & pressure tested csg. to 2500#, held good. Drilled out
Spotted acid (250 gal of 15% HCl w/double inhibitor.
2-10 - Perf'd 4763-88' - Testing

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Wesley L. Cannon* TITLE *clerk* DATE *2-22-72*

Orig. Signed by
John Runyan
Geologist

APPROVED BY _____ TITLE _____ DATE *Feb 25 1972*

CONDITIONS OF APPROVAL, IF ANY: