

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

CONSERVATION DIVISION
P. O. BOX 2086
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Free ☐
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REFINISH OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Name of Operator AMERADA HESS CORPORATION	7. Unit Agreement Name
2. Address of Operator Drawer D, Monument, New Mexico 88265	8. Form or Lease Name Mathers State Comm.
3. Location of Well UNIT LETTER <u>0D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>760</u> FEET FROM THE <u>West</u> LINE, SECTION <u>33</u> TOWNSHIP <u>11S</u> RANGE <u>33E</u> NMPM.	9. Well No. 1
10. Field and Pool, or Wildcat North Bagley - Penn	
11. Elevation (Show whether DF, RT, GR, etc.) 4290' DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☒	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to load hole w/water, run 8-5/8" pkr. on 2-3/8" tbg. & test for csg. leak at approx. 1905'. Perf. 8-5/8" csg. at 1925' w/two shots. Run cement retainer on 2-3/8" tbg. & set retainer at 1750' and attempt to circ. tracer dye to determine volume of cement needed. Squeeze csg. leak & perfs. w/400 sks. Class "C" w/additives, 150 sks. RFC & 200 sks. Class "H" cement. WOC & run bit on tbg. & drill out cement & retainer & test squeeze job w/1200#. Run tbg. to 9700' & swab down. Run drlg. bailer & remove bridge plug. Run retrievable bridge plug & pkr. on tbg. & test perfs. fr. 9750' to 10,973'. Evaluate, acidize if necessary & resume production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED EB Esker TITLE Supv. Adm. Ser. DATE August 8, 1979

APPROVED BY John W. Ramsey TITLE Geologist DATE AUG 13 1979

CONDITIONS OF APPROVAL, IF ANY:

EB Esker 9/30/79