

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Ralph Lowe	8. Farm or Lease Name Speight
3. Address of Operator P. O. Box 832, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> <u>510</u> FEET FROM THE <u>West</u> LINE AND <u>1980</u> FEET FROM THE <u>South</u> LINE, SECTION <u>7</u> TOWNSHIP <u>9-S</u> RANGE <u>35-E</u> NMPM.	10. Field and Pool, or Wildcat Vada (Penn)
15. Elevation (Show whether DF, RT, GR, etc.) 4203 GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well plugged as per verbal instructions of Mr. Joe Ramey on March 16th & 17th 1972 as follows:

Cast Iron Bridge Plug set @ 9750' with 4 sacks cement on top of plug; 50 sacks of cement in and out of stub of 5-1/2" casing at 4500'; 50 sacks cement in and out of 8-5/8" casing at 4060'; 10 sacks cement at surface w/regulation marker. Drilling Mud used between cement plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Nathan E. Clegg TITLE Agent DATE 3/21/72

APPROVED BY Nathan E. Clegg TITLE SEALOR DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR 22 1972

OIL CONSERVATION COMM.
HOBBS, N. M.