

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP (Other instruction
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 0189083-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Miller Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

10-9S-37E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER Dry	
2. NAME OF OPERATOR Delaware-Apache Corporation	
3. ADDRESS OF OPERATOR 1720 Wilco Building Midland, Texas 79701	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 660' FEL	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4007' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The Miller Federal #1 was drilled to 9737'. The following cement plugs were previously placed, putting subject well on temporary abandonment status:

30 sx 9576-9676
40 sx 7638-7738
30 sx 5150-5250
50 sx 4550-4650

The following plugs are proposed: 100 ft cement plug at stub of 8-5/8" casing.
If stub is below 2400', then set the cement plug from 2300-2400'.
100 ft cement plug at base of 13-3/8" casing
10 sx cement plug in top of 13-3/8" surface casing

Oral approval to plug and abandon given by Mr. A. Brown to L. Williams Aug 19, 1970.

18. I hereby certify that the foregoing is true and correct

SIGNED

Bonnie Husband

TITLE Production Clerk

DATE Aug. 19, 1970.

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED
AUG 20 1970

DATE

