

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0202980

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR AMOCO PRODUCTION COMPANY	8. FARM OR LEASE NAME MIDWEST H Federal
3. ADDRESS OF OPERATOR BOX 367, ANDREWS, TEXAS 79714	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State regulations. See also space 17 below.) At surface 660' FSL * 1980' FWL Sec. 25 (Unit N, SE 1/4 SW 1/4)	10. FIELD AND POOL, OR WILDCAT VADA PENN
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 25-9-33 NM PM
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4307' D.F.	12. COUNTY OR PARISH LEA
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT C. ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well physically P & A 10-24-75.

P & A as follows:

Set CIBP @ 9680' & Capped w/ 35' cement, AND SET 25 SACK plug loaded hole w/ mud. AT 8:00-8:15.
5 1/2" casing shot @ 4035, 4000', 4015, 3995, 2800', 1000' & 500'.
Unable to pull below 500'.
Recovered 500' of 5 1/2" and 500' of 8 7/8".

Spot 100' cement plug 5390'-5290' (T. Globe 5340')
Spot 50 SX " 4050'-3950'
" 50 " " 2850'-2750'
" 75 " " 2110'-2010'
" 75 " " 1050'-950'
" 75 " " 550'-450'
" 10' @ surface & erect P & A markers.

Final Cleanup & location to be drilled etc in accordance w/ good operating practices and land owner's desires.

18. I hereby certify that the foregoing is true and correct

SIGNED

Roy R. Roarkum

TITLE ADMINISTRATIVE ASSISTANT

DATE

OCT 28 1975

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

JAN 26 1976

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

044 USGS-H
1-DIV
1-SUSP
1-GRY