

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each completion. This form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

MAY 27 10 31 AM '69
11163 OFFICE OF THE COMMISSIONER

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	1810	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	1870	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt		T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	2540	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers		T. Devonian	T. Menefee	T. Madison
T. Queen		T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg		T. Montoya	T. Mancos	T. McCracken
T. San Andres	3830	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta	5242	T. McKee	Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	T.
T. Blinbry		T. Gr. Wash	T. Morrison	T.
T. Tubb	6715	T. Granite	T. Todilto	T.
T. Drinkard		T. Delaware Sand	T. Entrada	T.
T. Abo	7500	T. Bone Springs	T. Wingate	T.
T. Wolfcamp	8750	T.	T. Chinle	T.
T. Penn.		T.	T. Permian	T.
T. Cisco (Bough C)	9585	T.	T. Penn. "A"	T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	470		Surface Beds				
470	1810		Red Sand & Shale				
1810	1870		Anhy				
1870	2540		Anhy & Salt				DST #1 9560 - 9666/1 hr.
2540	2650		Sand & Shale				GTS 4 min.
2650	3830		Dol & Anhy				M 27 min.
3830	5242		Dol, Shale & Anhy				O & W 53 min.
5242	5320		Sand & Shale				Rec 1,004' oil, 90' wtr
5320	6715		Dol, Salt, Anhy & Shale				1 1/2 hr ISIP 1651#
6715	6850		Sand & Shale				2 hr FSIP 1626#
6850	7040		Sand, Shale & Anhy				IFP 770#
7040	7500		Anhy, Dol & Shale				FFP 1000#
7500	8750		Red & Green Shale & Dol				IHP 5061#
8750	9666		Lime & Shale				FHP 4997#