

Prod on testing allow.

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 1790	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt 2200	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt 2400	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates 2400	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers 2508	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen 2910	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracker _____
T. San Andres 3600	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta 5040	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb 6508	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo 7365	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp 8411	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) 9123	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1790	1790	Redbed & sand				
1790	2200	410	Anhydrite				
2200	2400	200	Salt				
2400	2508	108	Sand				
2508	3600	1092	Shaly & silty dolomite				
3600	5040	1440	Dolomite & lime				
5040	5120	80	Sand				
5120	6508	1388	Dolomite				
6508	6625	117	Sand				
7365	6625	740	Dolomite				
7365	7910	545	Shale				
7910	8411	501	Dolomite				
8411	9182	771	Lime & Shale				