

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-23072

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Keith Crouse

1. Type of Well:
OIL ☒
WELL ☐

GAS
WELL ☐

OTHER

2. Name of Operator
American Exploration Company

8. Well No.
1

3. Address of Operator
1331 Lamar, Suite 900 - Houston, TX 77010

9. Pool name or Wildcat
Flying M Bough South

4. Well Location
Unit Letter C : 660 Feet From The North Line and 1980 Feet From The West Line
Section 25 Township 95 Range 32E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/27/97 Set 5½" CIBP @ 8950' capw/25' cement.

5/29/97 Spot 25 sks cement at 5000'.

5/30/97 Cut 5½" casing at 3500', casing not free.

5/31/97 Spot 25 sks at 3550'. Tag at 3395'.

6/2/97 Perf. 5½" and 8-5/8" casing at 1675'. Squeeze 75 sks cement 100' out of 8-5/8" and 100' between 8-5/8" and 5½" and 100' in 5½" casing.

6/2/97 Perf. at 370'. PUMP 100 sks down 13-3/8" between 8-5/8" & 5½" casing. Tag at 230'.

6/3/97 Spot 10 sks cement from 30' to surface.

6/3/97 Install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Charley D. Gregg

TITLE

President

DATE

6/5/97

TYPE OR PRINT NAME

Charley D. Gregg - SNG Well P&A Services, LLC

TELEPHONE NO.

915/570-7685

(This space for state use)

ORIGINALS SENT BY

JOHN J. GREGG

APPROVED BY

GENERAL INSPECTOR

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

EW

AB
CP