SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO ORILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. 1. OIL X GAS WELL OTHER. 2. Name of Operator TEXAS PACIFIC OIL COMPANY, INC. 3. Address of Operator Post Office Box 1069 - Hobbs, New Mexico 58240 4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 4 TOWNSHIP 12-S RANGE 33-E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.)	Supersedes Old C-102 and C-103 Effective 1-1-65 Validicate Type of Lease State
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORWARD OF PERMIT OF TORRESPOND TO A DIFFERENT RESERVOIR. SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORWARD OF PERMIT OF TORRESPOND TO A DIFFERENT RESERVOIR. 1. OIL	Effective 1-1-65
U.S.G.S. LAND OFFICE OPERATOR SUNDRY NOTICES AND REPORTS ON WELLS (100 NOT USE THIS FORM FOR PREMITY - "(FORM ETTO)) FOR SUPERATOR RESERVOIR. 1. OIL	Undicate Type of Lease
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PERFORM TO METAL OF PERFORM PROPOSALS.) 1. OIL	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM OF PROPOSAGE TO BRILL ON TO DEEPEN ON FLUG BACK TO A DIFFERENT RESERVOIR. 1. OIL X GAS WELL OTHER. 2. Name of Operator TEXAS PACIFIC OIL COMPANY, INC. 3. Address of Operator Post Office Box 1069 - Hobbs, New Mexico 08240 4. Location of Well UNIT LETTER C	State X - 11 11 11 11 11 11 11 11 11 11 11 11 1
SUNDRY NOTICES AND REPORTS ON WELLS CONSTRUCT THIS FORM FOR PROPOSALS TO MELL ON TO SEPERATE SUCH PROPOSALS.] COLUMN WELL	
TEXAS PACIFIC OIL COMPANY, INC. 3. Address of Operator Post Office Box 1069 - Hobbs, New Mexico 08240 4. Location of Well UNIT LETTER C	State Oil & Gas Lease No.
TEXAS PACIFIC OIL COMPANY, INC. 3. Address of Operator Post Office Box 1069 - Hobbs, New Mexico 08240 4. Location of Well UNIT LETTER C	
TEXAS PACIFIC OIL COMPANY, INC. 3. Address of Operator Post Office Box 1069 - Hobbs, New Mexico 20240 4. Location of Well UNIT LETTER C	Unit Agreement Name
TEXAS PACIFIC OIL COMPANY, INC. 3. Address of Operator Post Office Box 1069 - Hobbs, New Mexico 08240 4. Location of Well UNIT LETTER C	
Post Office Box 1069 - Hobbs, New Mexico 08240 4. Location of Weil UNIT LETTER C	Farm or Lease Name
4. Location of Well UNIT LETTER C	Well No.
THE West LINE, SECTION 4 TOWNSHIP 12-S RANGE 33-E NAMPH. 15. Elevation (Show whether DF, RT, GR, etc.) 4251 GR Check Appropriate Box To Indicate Nature of Notice, Report or Other NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JQB OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimork) SEE RULE 1703. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9476', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize with 15% NE acid, using ball sealers while acidizing.	Field and Pool, or Wildcat Bagley Lower Penn
15. Elevation (Show whether DF, RT, GR, etc.) 12. 4251 GR Check Appropriate Box To Indicate Nature of Notice, Report or Other NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK X TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimork) SEE RULE 1703. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize we 15% NE acid, using ball sealers while acidizing.	Illining Tenn
Check Appropriate Box To Indicate Nature of Notice, Report or Other NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estiwork) SEE RULE 1703. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize we 15% NE acid, using ball sealers while acidizing.	
Check Appropriate Box To Indicate Nature of Notice, Report or Other NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimork) SEE RULE 1703. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize we 15% NE acid, using ball sealers while acidizing.	. County
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimork) SEE RULE 1703. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9476', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize we 15% NE acid, using ball sealers while acidizing.	
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimork) SEE RULE 1703. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize we 15% NE acid, using ball sealers while acidizing.	
TEMPORARILY ABANDON PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JQB OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimates work) SEE RULE 1703. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize we 15% NE acid, using ball sealers while acidizing.	
OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimork) see Rule 1103. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize w 15% NE acid, using ball sealers while acidizing.	ALTERING CASING
OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimates work) see Rule 1703. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize w 15% NE acid, using ball sealers while acidizing.	PLUG AND ABANDONMENT
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimate work) SEE RULE 1703. Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize w 15% NE acid, using ball sealers while acidizing.	
Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize w 15% NE acid, using ball sealers while acidizing.	
Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize w 15% NE acid, using ball sealers while acidizing.	
Upon approval we propose the following: 1. Move in, rig up and pull tubing, pump and vent string. 2. Perforate 9451', 9456', 9478', 9499', 9552', 9567', 9570', 9618', 9712', 9713', 9717', 9793', 9794', with 0.41" hole. (15 holes) 3. Run packer and retrievable bridge plug. 4. Set bridge plug at 9810'. 5. Spot acid over perforations and set packer at 9400', and acidize w 15% NE acid, using ball sealers while acidizing.	nated date of starting any proposed
	·
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNED TITLE Area Superintendent APPROVED BY JOHN W. RUMMAN TITLE Geologist	1