

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 9 2 20 PM '69

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	K-1852

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Sun Oil Company	8. Farm or Lease Name New Mexico "Q" State
3. Address of Operator P. O. Box 2792, Odessa, Texas 79760	9. Well No. 2
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM West LINE, SECTION 9 TOWNSHIP 11 S RANGE 34 E NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 4218 Gr.	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 7-1-69 ran 122 jts. 8 5/8" OD casing(79 jts. 24# J-55 8R ST&C #1 - 2589.22'), (43 jts. 28# H-40 8R ST&C #1 - 1405.11') seated at 4000'. Cemented with 300 sks Class C, 4% gel cement. Halliburton guide shoe at 4000', and Halliburton float collar at 3967'. WOC 19 hours. Tested 8 5/8" casing, 800#, 30 minutes, o.k.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>J. L. Edison</u>	TITLE <u>District Superintendent</u>	DATE <u>7-8-69</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>[Signature]</u>	DATE <u>7-10-69</u>
CONDITIONS OF APPROVAL, IF ANY:		