

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____ 1420'	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____ 1560'	T. Strawn _____ 10,140'	T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2250'	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 3355'	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____ 4948'	T. McKee _____	T. Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blaineby _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____ 6370'	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____ 7195'	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____ 8312'	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____ 9205'	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	1420'		Sand & Shales				DST #1 9045-9200'
1420'	2250'		Anhy, Sand & Shales				Rec. 40' mud
2250'	2370'		Sand				DST #2 9214 - 9362'
2370'	3555'		Anhy & Shale				Rec. 280' mud and
3555'	4948'		Dolo, Anhy & Shale				2535' salt water
4948'	6510'		Sand, Shale & Anhy				DST #3 9481 - 9552'
6510'	7195'		Dolo, Anhy & Shale				Rec. 110' mud
7195'	8312'		Red & Green Shale, Anhy & Dolo				DST #4 10,076 - 10,198'
8312'	TD		Lime & Shale				Rec. 150' mud
							DST #5 10,305 - 10,400'
							Rec. 570' gas and 210' gas cut mud