

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-073791

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
See "APPLICATION FOR PERMIT-1" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Coquina Oil Corporation

3. ADDRESS OF OPERATOR
200 Bldg. of Southwest, Midland, Texas 79701

4. LOCATION OF WELL (Report with care and in accordance with any State requirements.
See also space 17 below.)
At surface 1980' FWL & 660' FNL of Sec. 3

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 3

9. WELL NO.

1

10. FISH AND POOL OR WILDCAT

Vada Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T9S, R35E

14. PERMIT NO. 15. ELEVATIONS (Show whether DE, RT, GR, etc.)

G.L. 4173'

12. COUNTY OR PARISH 13. STATE

Lea

N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETION ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☒
(Other) ☐

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

The subject well was plugged and abandoned in the following manner on November 11, 1973.

1. Set one 5 1/2" cast iron bridge plug @ 9700' and one 5 1/2" cast iron bridge plug @ 4600'.
2. Cut 5 1/2" casing off at 4221' and pulled from well.
3. Spotted 90 sx. Cl. H cement plug from 4221' to 3921' via tubing.
4. Cut 8 5/8" casing off at 1018' and pulled from well.
5. Spotted 35 sx. Cl. H cement plug from 1025' to 925'.
6. Spotted 75 sx. Cl. H cement plug from 425' to 325'.
7. Placed 10 sx. Cl. H cement plug from 20' to surface.

Space between plugs filled with mud. DHM installed.

The U.S.G.S. will be notified when location is ready for final inspection.

18. I hereby certify that the foregoing is true and correct.

SIGNED J. T. Berry

TITLE Superintendent

DATE 11-21-73

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

APPROVED
SEP 4 1975

ANTHONY R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side