

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate  
(Other instructions on  
reverse side)

Form approved.  
Budget Bureau No. 42-11424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 073971

7. UNIT AGREEMENT NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. NAME OF OPERATOR McGrath & Smith, Inc.	3. ADDRESS OF OPERATOR 418 Bldg. of Southwest, Midland, Texas	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface UNIT C 1980' FWL & 660' FNL, Section 13	5. FIELD AND POOL, OR WILDCAT Vada Penn	6. SEC. T., R., M., OR BLM. AND SURVEY OR AREA Sec. 13, T9S, R35E	7. COUNTY OR PARISH Lea	8. STATE New Mexico
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, CR, etc.) GL 4173, KB 4184						

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Cementing Csg.-Well Record

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Spudded 11-20-69. Drilled 17½" hole to 375'. Cmt'd. 13-3/8"OD-48# Csg. @375'. Cmt. circulated. WOC 18 hrs. Tested 13-3/8" to 800 psi.-o.k. Drilled 11" hole to 4050'. Cmt'd. 8-5/8"-24#, 28#, 32# Csg. @4048' with 500 Sx. WOC 24 hrs. Tested 8-5/8" Csg. to 1000 psi.-o.k. Drilled 7-7/8" hole to TD 9810'. Cmt'd. 5½"-17#-N80 & J55 Csg. @9810' with 450 Sx. Top Cmt. @7852'. Perf. 2 JSPF 9757-63', 9768-84'. Acid 1000 gals. Swab tested. Ran 2-3/8"-N80 Tbg. Landed at 9703' with Pkr. at 9699'. Installed pumping equipment. Ready to pump 12-4-'69.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Superintendent

DATE 12-11-69

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DEC 18 1969

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse