

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. X	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry	7. Unit Agreement Name
2. Name of Operator King Resources Company	8. Farm or Lease Name
3. Address 300 Wall Towers West, Midland, Texas 79701	9. Name Wing McGuffin
4. Location UNIT LETTER I 1830 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 23 TOWNSHIP 9-S RANGE 32-E NMPM.	10. Field and Pool, or Wildcat South Flying "M" Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4315' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Drilled to depth of 9100' and temporarily abandoned 11-30-69.
2. Set cement plugs as follows:
3550 - 3650 with 35 sxs 7175 - 7245 with 25 sxs
4160 - 4230 with 25 sxs 8348 - 8418 with 25 sxs
4850 - 4920 with 25 sxs 9030 - 9100 with 25 sxs
3. Pulled and recovered 1611' of 8-5/8" 24# K-55 STC casing.
4. 4-16-70 - set cement plugs as follows: 1520 - 1620 with 25 sxs
325 - 425 with 35 sxs
surface - 30 with 10 sxs
5. Marker placed at surface. P&A 4-16-70.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED DE Jif	TITLE Drilling Foreman	DATE 6/22/70
APPROVED BY John W. Runyan	TITLE Geologist	DATE MAR 24 1971
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

JUN 23 1970

OIL CONSERVATION COMM.
HOBBBS. N. IA.