

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-1110
7. Unit Agreement Name
8. Farm or Lease Name Antweil State
9. Well No. 1
10. Field and Pool, or Wildcat Mescalero (San Andres)
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Mountain States Petroleum Corporation
3. Address of Operator P. O. Box 1936 Roswell, New Mexico 88201
4. Location of Well UNIT LETTER <u>P</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>27</u> TOWNSHIP <u>10S</u> RANGE <u>32</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4335 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

11-12-69 Spudded hole 8:30 PM. TD 375' Ran 8 jts (351.39') 8-5/8" 20# H-40 8R STC casing with coupling as shoe, set at 365' KB. Cemented with 220 sxs Class C (Incor) with 2% CaCl₂, used one wood top plug, pumped plug down with fresh water. Circulated 65 sxs to pits. Plug down 5:05 AM 11-13-69. WOC 18 hours. Pressured csg to 800# for 30 minutes. Pressure held.

Cement job by Dowell. Csg and cement job supervised by Conrad R. Appledorn, Engineer.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>R. J. Havenor</u>	TITLE <u>Geologist</u>	DATE <u>11-14-69</u>
APPROVED BY <u>Joe A. Roney</u>	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		