

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
<b>E-1516-1</b>

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>TEXACO Inc.</b>	8. Farm or Lease Name <b>New Mexico 'AR' State</b>
3. Address of Operator <b>P.O. Box 728, Hobbs, New Mexico 88240</b>	9. Well No. <b>3</b>
4. Location of Well UNIT LETTER <b>L</b> <b>660</b> FEET FROM THE <b>North</b> LINE AND <b>990</b> FEET FROM THE <b>West</b> LINE, SECTION <b>2</b> TOWNSHIP <b>11S</b> RANGE <b>37E</b> NMPM.	10. Field and Pool, or Wildcat <b>Echols (Devonian)</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3,955' DF</b>	12. County <b>Lea</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:



SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Ran cement retainer and set in 5-1/2" casing at 11,191'.
2. Squeezed below retainer w/100 sx Class 'C' cement and displace hole w/mud.
3. Spotted 45 sx plug @4805'.
4. Spotted 45 sx plug @1798'.
5. Spotted 10 sx plug @ surface.
6. Had leak between 8-5/8" & 11-3/4" casing.
7. Drilled out 30' plug in 8-5/8" casing and perforated 8-5/8" casing @1575'.
8. Squeezed w/150 sx Class 'C' cement.
9. Perforated 8-5/8" casing @350'.
10. Spotted 200 sx Class 'C' cement down 8-5/8" casing back to surface.
11. Install dry hole marker and clean location 5-5-73.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 	TITLE <b>Assistant District Superintendent</b>	DATE <b>May 23, 1973</b>
APPROVED BY 	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		