

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)E*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0145422-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brown

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Vada Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

17-9-36

12. COUNTY OR PARISH 13. STATE

Rposevelt

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

ROGER C. HANKS ~~OIL COMPANY~~

3. ADDRESS OF OPERATOR

c/o Hobbs Pipe & Supply, Box 2010, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Unit B, 660' FNL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spot a 25 sx plug to cover all existing perforations, 9802-9830'.
2. Load hole w/mud-laden fluids.
3. Pull casing from approximately 7,000'.
4. Spot a 35 sx plug @ 5-1/2" casing stub.
5. Spot a 35 sx plug from 5300-5400'.
6. Spot a 50 sx plug in and out of base of intermediate casing, 4130'.
7. Spot a 50 sx plug at stub of 8-5/8" casing, approx. 1000'.
8. Spot a 50 sx plug in and out of base of surface casing, 450'.
9. Spot a 10 sx plug at top & erect a 4" regulation marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

Stanley Hikin

TITLE

Agent

DATE 7/27/73

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUL 31 1973

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side