Form 9-331 May 1963)

## STATES THE UN D STATES DEPARTMEN OF THE INTERIOR Verse side

SUBMIT IN TRIPL (Other instructions	re-			Bud
verse side)	16	5.	LEAS	E DES

ø	Y	Form	8	ppro	već	1.			
		Budge	et i	Bu	eat	ı N	o. 4	2-R	1424
-		 							**

New Mexico 058311-B 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

	GEOL	OGICAL	SURVEY		
SUNDRY	NOTICES	AND	<b>REPORTS</b>	ON	<b>WELLS</b>

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME CA-SW-560 OTHER 8. FARM OR LEASE NAME MIDWEST OIL CORPORATION Federal I 9. WELL NO. 3. ADDRESS OF OPERATOR Box 2010, Hobbs, New Mexico 88240

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.) At surface

10. FIELD AND POOL, OR WILDCAT Vada Penn

1980' FEL & 810' FNL

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 18-9-35

14. PERMIT NO.

16.

WELL X

NAME OF OPERATOR

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

12. COUNTY OR PARISH | 13. STATE

Lea

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE	OF INTENTION TO:	SUBSEQUENT E	REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON® CHANGE PLANS	WATER SHUT-OFF  FRACTURE TREATMENT SHOOTING OR ACIDIZING  (Other)  (Note: Report results of my Completion or Recompletion	REPAIRING WELL  ALTERING CASING ABANDONMENT*  Ultiple completion on Well Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

- 1. Spotted a 25 sx cement plug @ TD to cover existing perforations.
- 2. Loaded hole w/mud-laden fluids.
- 3. Recovered production casing from 4,500'.
- 4. Spotted a 35 sx cement plug @ stub of 5-1/2" casing.
- 5. Spotted a 50 sx cement plug in and out of base of intermediate casing, set @ 4050'.
- 6. Shot & recovered 8-5/8" casing from approx. 1,250' & spotted a 50 sx plug.
- 7. Spotted a 50 sx cement plug in and out of base of 11-3/4", set 0 320'.
- 8. Spotted a 10 sx top-hole plug & erected a 4" regulation marker.
- 9. Well was plugged & abandoned on 7/12/73.

I hereby certify that the foregoing is true and corre	ct TITLE	Agent 7/24/73
(This space for Federal or State office use)		ADDROVED
APPROVED BY	TITLE	MAY 28 1975
•	See Instruction	MAY 28 1975 MAY 28 1975  BROWN  BROWN