	 ,		•
NO. OF COPIES RECEIVED			B
DISTRIBUTION	-		Form C-103 Supersedes Old
SANTA FE	NEW MEXICO OIL CON	SERVATION COMMISSION	C-102 and C-103
FILE		JERVATION COMMISSION	Effective 1-1-65
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE			State Fee X
OPERATOR			5, State Oil & Gas Lease No.
SUNI DO NOT USE THIS FORM FOR USE "APPLIE	DRY NOTICES AND REPORTS ON PROPOSALS TO DRILL OR TO DEEPEN OF PLUG BEATION FOR PERMIT - " (FORM C-101) FOR SUC	WELLS BACK TO A DIFFERENT RESERVOIR.	
OIL GAS WELL	OTHER-		7. Unit Agreement Name
2. Name of Operator			8. Form or Lease Name
Oil Development Company of Texas			SFPRR
3. Address of Operator			9. Well No.
900 Polk Street,	Amarillo, Texas 79101		10
٠		_	10. Field and Pool, or Wildcat
UNIT LETTER A	660 FEET FROM THE South	LINE AND FEET FROM	West Sawyer (San Andres
THE West LINE, SEC	TION 28 TOWNSHIP 9S	RANGE 37E NMPM.	
15, Elevation (Show whether DF, RT, GR, etc.) 3980' RKB			12. County Lea
Check	k Appropriate Box To Indicate N	lature of Notice. Report or Orl	ner Data
NOTICE OF	REPORT OF:		
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	
	·	OTHER	
OTHER			
17. Describe Proposed or Completed work) SEE RULE 1103.	Operations (Clearly state all pertinent deta	ails, and give pertinent dates, including	estimated date of starting any proposed
Cemented w/3 Cement circu	-23-70. Ran 10 jts 8-5/8' 25 sx Class H w/2% CaCl2. lated. Tested to 750 psi emented in accordance with	Plug down at 1:00 a.m. WOC 12 hours.	11-24-70.
_			

Spud date 11-23-70. Ran 10 jts 8-5/8" 20# casing, set at 417 Cemented w/325 sx Class H w/2% CaCl2. Plug down at 1:00 a.m. Cement circulated. Tested to 750 psi. WOC 12 hours.	' RKB. 11-24-70.			
Casing was cemented in accordance with NMOCC Option 2 as follows:				
1. Volume of slurry - 354 cu. ft., Southwestern, API Cl. 2. Approximate temperature of slurry - 72° F. 3. Estimated minimum formation temperature - 92° F. 4. Estimated cement strength at time of testing - 1310; 5. Actual time cement in place prior to starting test -	psi.			
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNED FAMY, W. Havel TITLE Petroleum Engineer	P			
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	DATE DEC 3 1970			

RECEIVED

2 1970

OIL CONSERVATION CO.AM.