(May 1963)	UN EDS		(Other Instance)		approved. t Bureau No. 42–R1 NATION AND SERIAL N
	GEOLOGICAI	_ SURVEY		NM 024987	2
	RY NOTICES AND rm for proposals to drill or to Use "APPLICATION FOR PER			6. IF INDIAN, AN	LLOTTEE OR TRIBE NA
1. 01L []. GAS				7. UNIT AGREEM	ENT NAME
2. NAME OF OPERATOR	OTHER			8. FARM OR LEA	SE NAME
	he Corporation	· · ·		Midwest F	ederal
3. ADDRESS OF OPERATOR	ildina Mi.	مناهد المستحد	*	9. WELL NO.	
1720 Wilco Bu 4. LOCATION OF WELL (Rep See also space 17 below.	port location clearly and in acc	lland, Texas ordance with any S	itate requirements.*	10. FIELD AND I	OOL, OR WILDCAT
At surface	•,			Vada Pe	
1980'	FS & EL			11. SEC., T., R., SURVEY O	M., OR BLE. AND R AREA
14. Permit No.	15. ELEVATIONS	(Show whether DF, 1	RT, GR, etc.)	<u>Sec. 5,</u> 12. COUNTY OR	<u>795, R34E</u> parishi 13btate
	Gr 4290.	.6'		Lea	New Mex
16.	Check Appropriate Box	To Indicate No	ature of Notice, Report, o	or Other Data	
Nor	TICE OF INTENTION TO:	1		SEQUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER C	ASING	WATER SHUT-OFF	REPA	IRING WELL
FRACTURE TREAT	MULTIPLE COMPL.	ETE	FRACTURE TREATMENT	ALTE	RING CASING
SHOOT OR ACIDIZE Repair Well	ABANDON* CHANGE PLANS		SHOOTING OR ACITIZING (Other) Casing	& cement test	DONMENT*
(Other)	CHANGE FLANS		(Other)	sults of multiple comp completion Report and	letion on Well
Spudded well at 9		-s 11-3/4" 4	•	ates, including estimat ertical depths for all i	emented with
Drld 15" hole to	384' and ran 10 jt s additives, circ	cs 11-3/4" 4 25 sx. WOC	2# H-40 casinc, s	et at 384'. C	emented with d casing to
0rld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-70 11" hole	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC '8' 32 & 24#	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-75 11" hole Gemented with 375	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC '8' 32 & 24#	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-75 11" hole Gemented with 375	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC '8' 32 & 24#	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-75 11" hole Gemented with 375	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC '8' 32 & 24#	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-75 11" hole Gemented with 375	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC '8' 32 & 24#	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-75 11" hole Gemented with 375	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC '8' 32 & 24#	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-75 11" hole Gemented with 375	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC '8' 32 & 24#	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-75 11" hole Gemented with 375	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC '8' 32 & 24#	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-75 11" hole Gemented with 375	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC '8' 32 & 24#	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-70 11" hole Gemented with 375 For 30 mins, held	384' and ran 10 jt s additives, circ held ok. . Ran 143 jts 8-5/ sx cement plus ac	25 sx. WOC (8' 32 & 24# ditives. WO	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395	et at 384'. C p BOPs, teste 8.22') set at s, tested to	d casing to
Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-70 11" hole Gemented with 375 For 30 mins, held	384' and ran 10 jt s additives, circ held ok Ran 143 jts 8-5/ sx cement plus ac ok. e foregoing is true and correct	25 sx. WOC (8' 32 & 24# ditives. WO	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395 C 18 hrs, Set BOP 18 hrs, Set BOP	et at 384'. C p BOPs, teste 8.22') set at s, tested to	d casing to 3951'. 1500#,
 Orld 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-70 11" hole cemented with 375 for 30 mins, held 18. I hereby certify that th SIGNED	384' and ran 10 jt s additives, circ held ok Ran 143 jts 8-5/ sx cement plus ac ok. e foregoing is true and correct	25 sx. WOC (8' 32 & 24# iditives. WO :t TITLE	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395 C 18 hrs, Set BOP 18 hrs, Set BOP	et at 384'. C p BOPs, teste 8.22') set at s, tested to	d casing to 3951'. 1500#,
 Prid 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-70 11" hole cemented with 375 for 30 mins, held 18. I hereby certify that th SIGNED 	384' and ran 10 jt s additives, circ held ok. Ran 143 jts 8-5/ sx cement plus ac ok. e foregoing is true and correct us function of the second correct or State office use)	25 sx. WOC (8' 32 & 24# ditives. WO	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395 C 18 hrs, Set BOP Note: Note: N	et at 384'. C p BOPs, teste 8.22') set at s, tested to DATE OR DECORD	d casing to 3951'. 1500#,
 Prid 15" hole to 850 sx cement plu 800# for 30 mins, 2-3-70 11" hole cemented with 375 for 30 mins, held 18. I hereby certify that the SIGNED	384' and ran 10 jt s additives, circ held ok. Ran 143 jts 8-5/ sx cement plus ac ok. e foregoing is true and correct us function of the second correct or State office use)	25 sx. WOC (8' 32 & 24# iditives. WO :t TITLE	2# H-40 casing, s 18 hrs. Nippled u K-55 casing (395 C 18 hrs, Set BOP 18 hrs, Set BOP	et at 384'. C p BOPs, teste 8.22') set at s, tested to DATE OR DECORD	d casing to 3951'. 1500#,

·~`