

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
PHLC	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101, FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☒ Fee ☐
1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-		5. State Oil & Gas Lease No.
2. Name of Operator Belco Development Corporation		7. Unit Agreement Name
3. Address of Operator 10,000 Old Katy Road Suite 100, Houston, Texas 77055		6. Farm or Lease Name Warren American St. Com.
4. Location of Well UNIT LETTER <u>M</u> <u>510</u> FEET FROM THE <u>West</u> LINE AND <u>660</u> FEET FROM THE <u>South</u> LINE, SECTION <u>27</u> TOWNSHIP <u>11-S</u> RANGE <u>33-E</u> N.M.P.M.		9. Well No. 1
15. Elevation (Show whether DF, KT, GR, etc.) 4271 KB		10. Field and Pool, or Valued Bagley, N (Penn)
		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOB ☐ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☒
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.			

Bridge plug set at 9101' on 4-27-76. Perforations above BP located at 8633' - 43' & 9061 - 68'.

Plugging procedure: Operations started 11-30-83

- Set CIBP @ 8610'. TIH w/tbg. open ended. Loaded & circulated hole from 8610' with 10#/gal. brine mud. Spotted 20 sx cmt. plug from 8610'-8378' in 4 -1/2" 11.6#/ft. N-80 csg.
- Spotted 20 sx. cmt. plug in 4-1/2" csg. from 7510'-7278'.
- Spotted 20 sx. cmt. plug in 4-1/2" csg. from 5120'-4888'.
- Cut 4-1/2" csg. @ 3731' & pulled.
- TIH w/2-3/8" OD tbg. & spot 35 sx. cmt. plug from 3770'-3656' (39' inside of 4-1/2" csg. & 75' inside 8-5/8" csg.) Tagged cmt. top after 3 hrs. @ 3640'.
- TOH w/tbg. to 1500' & circ. hole w/10#/gal. brine mud. Spotted 35 sx. cmt. plug from 1500'-1586'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

NO. Carl M. Houser TITLE Prod. Supt DATE 1/3/84

NOVED BY David Caton TITLE OIL & GAS INSPECTOR DATE APR 9 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 5 1984

O.C.D.
HOBBS OFFICE