

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 069300

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mobil Atlantic Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Allison

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T9S, R36E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Discovery Operating, Inc.

3. ADDRESS OF OPERATOR

504 Gulf Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

554' FSL and 766' FEL, Section 3, T9S R36E Unit P

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

DF 4095'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Bridge Plug set @ 9220' w/35' cement on top.
2. Set Bridge Plug @ 8900' w/ 4 sacks cement on top.
3. 25 sacks cement plug set @ 7463-7563'.
4. Cut 4 1/2" csg. and pulled 5871' 4 1/2" csg.
5. Set 35 sack cement plug 5821-5921'.
6. Set 35 sack cement plug 4100-4200' (Base of 8 5/8" csg @ 4150').
7. Cut and pulled 951' 8 5/8" csg.
8. Set 50 sack cement plug 937-1037'.
9. Set 50 sack plug 400-500' (Base of 12 3/4" csg. 450')
10. Set 10 sack plug at surface.
11. Install marker; fill cellar and pits, level battery grade and hole is loaded with brine containing 25 sacks gel per 100 barrels.

Completed plugging 8/26/74 Finished clean up during 1975.

18. I hereby certify that the foregoing is true and correct.

SIGNED Don L. Parks

TITLE Vice President

DATE

3/10/76

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side